

Photo Luminescent Tape FG series

Item Code: RS-2-FG301-HRS



FOB Price: \$10.31/sq.m

Mini Order: 5 rolls

Average Rating: 66.0lb (30kg)

Inquire Now

Overview

Description:

This is soft PET film made from aluminate, silicate, with adhesive and liner paper on the back side. This film does not contain any nontoxic radioactive element, and is of bright illumination, long life and duration, environment friendly, stable chemical property, power saver, non-tear, digital cut. It can illuminate for 5 hours after shining in a short time.

Feature:

- . Have stable chemical properties, non-toxic, non-radioactive.
- . High initial luminance.
- . Long duration.
- . Good extensibility.
- . Can be used in bad weather.
- . Good for computer cutting.
- . Feasible Operating Temperature: 18-28°C.
- . Service Life: Indoor 20 years, outdoor 7 years.
- . Specification: 48.8"*149.9' (1.24m*45.7m) per roll.
- . Colour: light green.









Application:

Safe guiding, placename signs, traffic signs, mine, fire fighting.

Specifications

Technical sppecifications

Surface Film PET type Thickness of film 0.16mm Thickness of Glue 0.04mm Thickness of Release Paper 0.18mm Total thickness of products 0.38mm

Above thickness is with allowance of 5% more or less

Weight of Release Paper 165g/sqm with 5% more or less

Type of Adhesive Pressure-Sensitive Type

after sticking to the board for 24 hours, at the condition of 1.8lb (0.8kg), 5mil, total length Strength of Adhesive

10cm, the falling Length?0.8" (2cm)

10 °C-30 °C Operation temperature

Working temperature -20?- 60? (After sticking to the board for at least 7 days)

0 °C-30 °C Storage temperature























Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com